



**midas**  
MILEAGE

EXPORT DESIGNS 2008



## Precured Treads

Made from high mileage compounds, our treads have been accepted the world over and tested on all road conditions.



## Black Vulcanising Solution

Available as **Thicker** and **Ready to use** solution. Compatible with both precured and hot process.



## Bonding Gum

Available for 99°C, 110°C and 125°C operations. Our gum is made from 100% natural rubber to increase tack. Available in customer specified sizes also. Can be used to fill nail holes and repair injured parts of casing.



## Camel Back

Increased scorch safety to maximise shelf life. Different compounds available for different uses including (Truck, Tractor and OTR). Available in customer specified sizes.



**midas**  
MILEAGE



## Orbi Strip

Available for Truck, OTR and car applications.



## Rope Rubber

To be used in rubber extruder guns to repair rasping area. Provides excellent process safety and tack.

## Wicking Pad



**midas**  
MILEAGE

## Outer and Inner Envelopes

Heat resistant envelopes for ease of use and long life.






## TRACTION



M-2

| mm  | in    | mm   | kg/m | kg   |
|-----|-------|------|------|------|
| 250 | 10.50 | 18.0 | 4.88 | 51.0 |
| 240 | 3.75  | 18.0 | 4.37 | 16.4 |

MIDAS  
MILEAGE



GRTA

| mm  | mm  | in   | mm   | kg/m | kg   |
|-----|-----|------|------|------|------|
| 250 | 275 | 3.28 | 17.0 | 4.82 | 15.8 |
| 240 | 270 | 3.28 | 17.0 | 4.70 | 15.4 |
| 230 | 280 | 3.28 | 17.0 | 4.58 | 15.0 |

MIDAS  
MILEAGE



M-4

| mm  | in    | mm   | kg/m | kg   |
|-----|-------|------|------|------|
| 260 | 10.50 | 18.0 | 5.10 | 53.5 |
| 250 | 10.50 | 18.0 | 4.71 | 49.5 |
| 240 | 10.50 | 18.0 | 4.55 | 47.8 |
| 230 | 10.50 | 18.0 | 4.35 | 45.7 |

MIDAS  
MILEAGE



M-1

| mm  | in    | mm   | kg/m | kg   |
|-----|-------|------|------|------|
| 260 | 10.50 | 19.0 | 5.05 | 53.0 |
| 250 | 10.50 | 19.0 | 4.93 | 51.8 |
| 240 | 10.50 | 19.0 | 4.72 | 49.8 |
| 230 | 10.50 | 19.0 | 4.43 | 46.5 |


MIDAS  
MILEAGE



M-8

| mm  | in    | mm   | kg/m | kg   |
|-----|-------|------|------|------|
| 260 | 10.50 | 19.0 | 4.87 | 51.1 |
| 250 | 10.50 | 19.0 | 4.70 | 49.4 |
| 240 | 10.50 | 19.0 | 4.52 | 47.5 |


MIDAS  
MILEAGE



**M-10**

| mm  | in    | mm   | Agile | kg   |
|-----|-------|------|-------|------|
| 280 | 3.40  | 21.0 | 6.56  | 22.3 |
| 270 | 3.40  | 21.0 | 6.09  | 20.7 |
| 260 | 10.50 | 19.0 | 5.16  | 54.2 |
| 250 | 10.50 | 19.0 | 4.92  | 51.7 |
| 240 | 10.50 | 19.0 | 4.66  | 48.9 |
| 230 | 10.50 | 19.0 | 4.52  | 47.5 |
| 220 | 3.28  | 15.0 | 3.41  | 11.2 |
| 210 | 3.28  | 15.0 | 3.32  | 10.9 |


**midas MILEAGE**



**M-19**

| mm  | in   | mm   | Agile | kg   |
|-----|------|------|-------|------|
| 240 | 3.75 | 19.0 | 4.99  | 18.7 |
| 230 | 3.75 | 19.0 | 4.50  | 17.2 |


**midas MILEAGE**



**M-12**

| mm  | in   | mm   | Agile | kg   |
|-----|------|------|-------|------|
| 270 | 3.73 | 17.0 | 5.50  | 20.5 |
| 260 | 3.73 | 17.0 | 5.28  | 19.7 |


**midas MILEAGE**



**ZZ**

| mm  | in    | mm   | Agile | kg   |
|-----|-------|------|-------|------|
| 250 | 10.50 | 18.0 | 4.62  | 48.5 |
| 240 | 10.50 | 18.0 | 4.23  | 44.4 |
| 230 | 10.50 | 18.0 | 3.95  | 41.5 |

**midas MILEAGE**

**M-5 (B)**

| mm  | mm  | in    | mm   | Agile | kg   |
|-----|-----|-------|------|-------|------|
| 305 | —   | 10.50 | 15.0 | 5.62  | 59.0 |
| 295 | 325 | 3.73  | 15.0 | 5.63  | 21.0 |

**midas MILEAGE**



| mm  | mm  | in    | mm   | kg/in | kg   |
|-----|-----|-------|------|-------|------|
| 320 | 380 | 10.50 | 13.0 | 5.48  | 57.5 |
| 295 | 325 | 3.45  | 13.0 | 4.78  | 16.5 |

**MIDAS**  
**MILEAGE**



| mm  | mm  | in   | mm   | kg/in | kg   |
|-----|-----|------|------|-------|------|
| 295 | 330 | 3.30 | 15.0 | 5.24  | 17.3 |

**MIDAS**  
**MILEAGE**



| mm  | mm  | in    | mm   | kg/in | kg   |
|-----|-----|-------|------|-------|------|
| 260 | 300 | 10.50 | 16.0 | 5.48  | 57.8 |
| 250 | 290 | 10.50 | 16.0 | 5.24  | 55.0 |

**MIDAS**  
**MILEAGE**



| mm  | mm  | in   | mm   | kg/in | kg   |
|-----|-----|------|------|-------|------|
| 295 | 330 | 3.30 | 13.5 | 4.79  | 15.8 |
| 287 | 320 | 3.30 | 13.5 | 4.85  | 16.0 |

**MIDAS**  
**MILEAGE**



| mm  | mm  | in   | mm   | kg/in | kg   |
|-----|-----|------|------|-------|------|
| 295 | 330 | 3.34 | 15.0 | 5.78  | 19.3 |

**MIDAS**  
**MILEAGE**



| mm  | mm  | in    | mm   | kg/in | kg   |
|-----|-----|-------|------|-------|------|
| 295 | 335 | 3.28  | 13.0 | 4.57  | 15.0 |
| 285 | 325 | 10.50 | 13.0 | 4.55  | 47.8 |

**MIDAS**  
**MILEAGE**



WINTER



M-20

MIDAS

| mm  | in   | mm   | kg/m <sup>2</sup> | kg   |
|-----|------|------|-------------------|------|
| 270 | 3.73 | 20.0 | 5.63              | 21.0 |
| 260 | 3.73 | 20.0 | 5.50              | 20.5 |
| 250 | 3.73 | 20.0 | 5.36              | 20.0 |
| 240 | 3.45 | 20.0 | 5.07              | 17.5 |
| 230 | 3.45 | 20.0 | 4.93              | 17.0 |

MIDAS MILEAGE



DNM

MIDAS

| mm  | in   | mm   | kg/m <sup>2</sup> | kg   |
|-----|------|------|-------------------|------|
| 260 | 3.30 | 21.0 | 6.64              | 21.9 |
| 250 | 3.30 | 21.0 | 6.52              | 21.5 |
| 240 | 3.30 | 21.0 | 6.30              | 20.8 |

MIDAS MILEAGE



MNW

MIDAS

| mm   | in    | mm   | kg/m <sup>2</sup> | kg   |
|------|-------|------|-------------------|------|
| 230  | 10.50 | 22.0 | 5.19              | 54.5 |
| *180 | 10.50 | 17.0 |                   |      |

MIDAS MILEAGE

\*coming soon



M-17

MIDAS

| mm  | in   | mm   | kg/m <sup>2</sup> | kg   |
|-----|------|------|-------------------|------|
| 250 | 3.75 | 22.0 | 6.00              | 22.5 |
| 240 | 3.75 | 22.0 | 5.81              | 21.8 |

MIDAS MILEAGE



MNW-S

MIDAS

| mm   | in    | mm   | kg/m <sup>2</sup> | kg |
|------|-------|------|-------------------|----|
| *215 | 10.50 | 15.0 |                   |    |

MIDAS MILEAGE

\*coming soon



## BUS & LIGHT TRUCK



| mm  | in    | mm   | Agiles | kg   |
|-----|-------|------|--------|------|
| 200 | 10.50 | 13.0 | 2.89   | 30.3 |
| 190 | 10.50 | 13.0 | 3.05   | 32.0 |
| 180 | 10.50 | 13.0 | 2.57   | 27.0 |
| 170 | 10.50 | 13.0 | 2.44   | 25.8 |

MIDAS MILEAGE



| mm  | in   | mm   | Agiles | kg   |
|-----|------|------|--------|------|
| 230 | 3.75 | 15.0 | 4.37   | 16.4 |
| 215 | 3.75 | 15.0 | 4.00   | 15.0 |
| 212 | 3.23 | 10.0 | 2.78   | 9.0  |
| 190 | 3.15 | 11.0 | 2.70   | 8.6  |

MIDAS MILEAGE

\*coming soon



| mm  | in    | mm   | Agiles | kg   |
|-----|-------|------|--------|------|
| 230 | 10.50 | 16.5 | 4.06   | 42.6 |
| 220 | 10.50 | 16.5 | 3.79   | 39.8 |
| 215 | 10.50 | 16.5 | 3.81   | 40.0 |
| 204 | 10.50 | 16.5 | 3.60   | 37.8 |

MIDAS MILEAGE








| mm  | mm  | in    | mm   | Agiles | kg   |
|-----|-----|-------|------|--------|------|
| 240 | 270 | 10.50 | 13.0 | 3.86   | 40.5 |
| 230 | 260 | 10.50 | 13.0 | 3.71   | 39.0 |






MIDAS MILEAGE



| mm  | in    | mm  | Agiles | kg   |
|-----|-------|-----|--------|------|
| 220 | 10.50 | 9.5 | 2.75   | 28.9 |
| 210 | 10.50 | 9.5 | 2.57   | 27.0 |






MIDAS MILEAGE

|  mm |  in |  mm |  Ag/m |  kg |
|--|--|--|--|--|
| 220  | 10.50  | 12.0   | 3.22   | 33.8   |
| 215  | 10.50  | 12.0   | 3.10   | 32.5   |
| 203  | 10.50  | 12.0   | 2.81   | 30.6   |






|  mm |  in |  mm |  Ag/m |  kg |
|--|--|--|---|--|
| 255  | 3.73   | 14.0   | 4.58  | 17.1   |
| 240  | 10.50  | 14.0   | 4.18  | 43.9   |
| 235  | 3.73   | 14.0   | 4.00  | 14.9   |
| 230  | 10.50  | 14.0   | 4.06  | 42.6   |
| 225  | 3.73   | 15.0   | 4.00  | 14.9   |
| 220  | 10.50  | 15.0   | 4.08  | 42.8   |
| 215  | 3.73   | 14.5   | 3.81  | 14.2   |
| 210  | 10.50  | 15.0   | 3.71  | 38.0   |
| 200  | 3.20   | 15.0   | 3.63  | 11.6   |
| 195  | 3.20   | 15.0   | 3.59  | 11.5   |
| 185  | 3.15   | 13.5   | 3.17  | 10.0   |
| 158  | 2.51   | 11.5   | 2.19  | 5.5  |
| 148  | 2.51   | 11.5   | 1.99  | 5.0  |













**MIXED APPLICATION**






|  mm |  in |  mm |  Ag/m |  kg |
|--|--|--|---|--|
| 240  | 3.75   | 14.5   |   |  |
| 230  | 3.75   | 14.5   |   |  |
| 220  | 10.50  | 18.5   | 3.90  | 41.0   |
| 215  | 10.50  | 18.5   | 3.77  | 38.6   |






\*coming soon






|  mm |  in |  mm |  Ag/m |  kg |
|--|--|--|--|--|
| 240  | 10.50  | 17.0   | 4.09   | 42.9   |
| 230  | 10.50  | 17.0   | 3.91   | 41.1   |
| 220  | 10.50  | 17.0   | 3.79   | 38.8   |






|  mm |  in |  mm |  Ag/m |  kg |
|--|--|--|---|--|
| 230  | 3.75   | 15.0   | 4.05  | 15.2   |
| 215  | 3.75   | 15.0   | 3.76  | 14.1   |






|  | <b>M-16 (H)</b> |  |  |  |  |
|--|-----------------|---|---|---|---|
| mm   | in              | mm  | kg/m <sup>2</sup>   | kg  |   |
| 270  | 3.40            | 21.0  | 6.88  | 22.7  |   |
| 260  | 10.50           | 21.0  | 6.15  | 64.6  |   |
| 250  | 10.50           | 21.0  | 6.14  | 64.5  |   |
| 240  | 10.50           | 21.0  | 6.71  | 60.0  |   |

|  | <b>M-16 (L)</b> |  |  |  |  |
|---|-----------------|---|---|--|---|
| mm  | in              | mm  | kg/m <sup>2</sup>   | kg   |   |
| 280   | 10.50           | 18.0  | 5.46  | 57.3   |   |
| 250   | 10.50           | 18.0  | 5.31  | 55.8   |   |
| 240   | 10.50           | 18.0  | 4.71  | 49.5   |   |






|  | <b>MML (H)</b> |  |  |  |  |
|---|----------------|---|---|---|---|
| mm  | in             | mm  | kg/m <sup>2</sup>   | kg  |   |
| 270   | 3.40           | 21.0  | 6.47  | 22.0  |   |
| 260   | 10.50          | 21.0  | 5.99  | 62.9  |   |
| 250   | 10.50          | 21.0  | 5.76  | 60.5  |   |
| 240   | 10.50          | 21.0  | 5.41  | 56.8  |   |






|  | <b>MML (L)</b> |  |  |  |  |
|--|----------------|---|---|--|---|
| mm   | in             | mm  | kg/m <sup>2</sup>   | kg   |   |
| 260  | 10.50          | 18.0  | 5.30  | 55.6   |   |
| 250  | 10.50          | 18.0  | 5.10  | 53.5   |   |
| 240  | 10.50          | 18.0  | 4.76  | 50.0   |   |
| 230  | 10.50          | 17.0  | 4.66  | 48.9   |   |
| 220  | 10.50          | 17.0  | 4.28  | 44.7   |   |
| 210  | 3.25           | 14.0  | 3.38  | 11.0   |   |






|  | <b>MAXIMUS (H)</b> |  |  |  |  |
|--|--------------------|---|---|---|---|
| mm   | in                 | mm  | kg/m <sup>2</sup>   | kg  |   |
| 265  | 10.50              | 16.0  | 4.90  | 51.5  |   |
| 250  | 10.50              | 16.0  | 4.53  | 47.8  |   |
| 240  | 10.50              | 16.0  | 4.46  | 46.8  |   |
| 235  | 10.50              | 16.0  | 4.90  | 51.5  |   |
| 235  | 10.50              | 18.0  | 4.10  | 43.0  |   |
| 230  | 10.50              | 16.0  | 4.22  | 44.3  |   |
| 225  | 3.73               | 16.0  | 4.10  | 15.3  |   |
| 220  | 10.50              | 16.0  | 4.05  | 42.5  |   |






|  | <b>MAXIMUS (L)</b> |  |  |  |  |
|---|--------------------|---|---|--|---|
| mm  | in                 | mm  | kg/m <sup>2</sup>   | kg   |   |
| 250   | 7.50               | 14.0  | 4.27  | 32.0   |   |
| 240   | 7.50               | 14.0  | 3.93  | 29.5   |   |
| 235   | 10.50              | 14.0  | 3.87  | 38.5   |   |
| 230   | 10.50              | 14.0  | 3.57  | 37.5   |   |
| 225   | 7.50               | 14.0  | 3.51  | 26.3   |   |
| 220   | 3.73               | 14.0  | 3.54  | 13.2   |   |
| 215   | 10.50              | 15.0  | 3.63  | 38.1   |   |
| 210   | 10.50              | 15.0  | 3.38  | 35.5   |   |
| 205   | 3.75               | 14.0  | 3.09  | 11.8   |   |
| 194   | 3.15               | 13.5  | 3.17  | 10.0   |   |
| 187   | 3.15               | 13.5  | 3.05  | 8.6  |   |
| 180   | 2.51               | 11.0  | 2.23  | 5.8  |   |
| 150   | 2.51               | 11.0  | 1.99  | 5.0  |   |


\*coming soon

| <b>PC1</b> |      |  |  |  |  |  |
|------------|------|---|---|---|---|---|
| mm         | in   | mm  | mm  | Agile   | kg  |   |
| 240        | 3.73 | 15.0  | 4.28  | 15.9  |   |   |
| 230        | 3.73 | 15.0  | 4.02  | 15.0  |   |   |
| 215        | 3.73 | 15.0  | 3.83  | 14.3  |   |   |






| <b>ZL-2</b> |       |  |  |  |  |  |
|-------------|-------|---|---|---|---|---|
| mm          | in    | mm  | mm  | Agile   | kg  |   |
| 220         | 10.50 | 21.0  | 4.70  | 48.4  |   |   |
| 210         | 10.50 | 21.0  | 4.38  | 45.8  |   |   |
| 200         | 10.50 | 21.0  | 4.19  | 44.0  |   |   |






| <b>Z-LUG (H)</b> |       |  |  |  |  |  |
|------------------|-------|---|---|---|---|---|
| mm               | in    | mm  | mm  | Agile   | kg  |   |
| 240              | 10.50 | 21.0  | 5.82  | 59.0  |   |   |
| 240              | 10.50 | 19.0  | 5.00  | 52.5  |   |   |
| 230              | 10.50 | 19.0  | 4.70  | 49.3  |   |   |






| <b>Z-LUG (L)</b> |      |  |  |  |  |  |
|------------------|------|---|---|---|---|---|
| mm               | in   | mm  | mm  | Agile   | kg  |   |
| 250              | 3.73 | 14.5  | 4.21  | 15.7  |   |   |
| 240              | 3.73 | 16.0  | 4.45  | 16.6  |   |   |
| 235              | 3.73 | 14.0  | 3.70  | 13.8  |   |   |
| 230              | 3.73 | 14.0  | 3.67  | 13.7  |   |   |
| 225              | 3.73 | 16.0  | 4.08  | 15.2  |   |   |
| 220              | 3.73 | 16.0  | 4.02  | 15.0  |   |   |
| 215              | 3.73 | 16.0  | 3.97  | 14.8  |   |   |
| 210              | 3.73 | 16.0  | 3.89  | 14.5  |   |   |
| 205              | 3.23 | 14.0  | 3.40  | 11.0  |   |   |
| 195              | 3.15 | 15.0  | 3.62  | 11.4  |   |   |
| 180              | 2.51 | 13.0  | 2.43  | 6.1   |   |   |
| 124              | 2.29 | 12.0  | 1.66  | 3.8   |   |   |








**OFF ROAD**






| <b>GPZH</b> |       |  |  |  |  |  |
|-------------|-------|---|---|---|---|---|
| mm          | in    | mm  | mm  | Agile   | kg  |   |
| 270         | 10.50 | 32.0  | 8.31  | 87.3  |   |   |
| 260         | 10.50 | 19.0  | 5.48  | 57.5  |   |   |
| 250         | 10.50 | 22.0  | 5.91  | 62.1  |   |   |
| 240         | 10.50 | 19.0  | 4.86  | 51.0  |   |   |






| LOG LUGGER |      |  |  |  |  |  |
|------------|------|---|---|---|---|---|
| mm         | in   | mm  | kg/m <sup>2</sup>   | kg  |   |   |
| 240        | 3.73 | 21.0  | 5.38  | 20.0  |   |   |
| 220        | 3.73 | 17.0  | 4.07  | 15.2  |   |   |
| 210        | 3.73 | 15.0  | 3.48  | 12.9  |   |   |








| M-3 |      |  |  |  |  |  |
|-----|------|---|---|---|--|---|
| mm  | in   | mm  | kg/m <sup>2</sup>   | kg  |  |   |
| 240 | 10.5 | 18.0  | 4.80  | 51.5  |  |   |










| DL  |      |  |  |  |  |  |
|-----|------|---|---|---|--|---|
| mm  | in   | mm  | kg/m <sup>2</sup>   | kg  |  |   |
| 280 | 3.86 | 16.0  | 5.44  | 21.0  |  |   |








| DB TREAD |       |  |  |  |  |  |
|----------|-------|---|---|---|---|---|
| mm       | in    | mm  | kg/m <sup>2</sup>   | kg  |   |   |
| 305      | 10.50 | 12.60   | 4.76  | 50.0  |   |   |
| 230      | 3.10  | 16.00   | 4.45  | 13.8  |   |   |
| 205      | 3.25  | 22.00   | 5.17  | 16.8  |   |   |
| 200      | 2.40  | 14.00   | 3.33  | 8.0   |   |   |
| 175      | 3.20  | 14.00   | 3.30  | 10.6  |   |   |
| 140      | 2.40  | 14.00   | 2.40  | 5.8   |   |   |

| GARTIC |      |  |  |  |  |  |
|--------|------|---|---|---|--|---|
| mm     | in   | mm  | kg/m <sup>2</sup>   | kg  |  |   |
| 330    | 3.86 | 15.5  | 6.89  | 26.6  |  |   |
| 295    | 3.86 | 15.5  | 5.93  | 22.9  |  |   |

| <br><b>GRML</b><br> |  mm |  mm |  mm |  Agility |  kg |
|--|--|--|--|---|--|
|  | 320  | 3.86   | 20.0   | 6.09  | 23.5   |
| 300  | 3.86   | 18.0   | 5.41   | 20.9  |  |
| 290  | 3.86   | 18.0   | 5.18   | 20.0  |  |

| <br><b>MOTR</b><br> |  mm |  mm |  mm |  Agility |  kg |
|---|--|--|--|---|--|
|   | *550   | 4.16   | 23.0   | 5.60  | 46.6   |

\* Available as 275 mm + 275 mm = 550 mm

| <br><b>MZL</b><br> |  mm |  mm |  mm |  Agility |  kg |
|--|--|--|--|---|--|
|  | 390  | 3.50   | 16.0   | 6.28  | 22.0   |

A STAR EXPORT HOUSE

## GENERAL RUBBERS

P. John Zachariah Building,  
Kottayam - 686 001, Kerala, India.

Phone: 91-481-2561215

Fax: 91-481-2561155

Website: [www.midas.co.in](http://www.midas.co.in)

E-mail: [info@midastreads.com](mailto:info@midastreads.com) (Export Division)

[sales@midastreads.com](mailto:sales@midastreads.com) (Domestic Division)

**midas**  
MILEAGE